













A

Extruded heatsinks for PCB mounting

- single solder pin
- profile **SK 437** → A 28
- special lengths and drillings on request
- **L** = solderable pin

			
art. no.	↔ [mm]	R _{th} [K/W]	⊕
SK 437 25 STC	25	24	TO 218/ TO 220/ TO 247/ TO 248
SK 437 30 STC	30	22	
SK 437 35 STC	35	18	
SK 437 50 STC	50	14	
			
art. no.	↔ [mm]	R _{th} [K/W]	⊕
SK 437 25 STS	25	24	TO 218/ TO 220/ TO 247/ TO 248
SK 437 30 STS	30	22	
SK 437 35 STS	35	18	
SK 437 50 STS	50	14	
surface:		black anodised	

- double solder pin
- profile **SK 437** → A 28
- special lengths and drillings on request
- **L** = solderable pin

			
art. no.	↔ [mm]	R _{th} [K/W]	⊕
SK 437 25 STC 2	25	24	TO 218/ TO 220/ TO 247/ TO 248
SK 437 30 STC 2	30	22	
SK 437 35 STC 2	35	18	
			
art. no.	↔ [mm]	R _{th} [K/W]	⊕
SK 437 25 STS 2	25	24	TO 218/ TO 220/ TO 247/ TO 248
SK 437 30 STS 2	30	22	
SK 437 35 STS 2	35	18	
surface:		black anodised	

N

A 133
EL.ITALIA

 www.elitaliaweb.it
 info@elitaliaweb.it
 +39 0233611626
